

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
23 March 2006 (23.03.2006)

PCT

(10) International Publication Number  
**WO 2006/031386 A3**

(51) International Patent Classification:  
*F16L 15/00* (2006.01)

(21) International Application Number:  
PCT/US2005/029870

(22) International Filing Date: 23 August 2005 (23.08.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/608,849 10 September 2004 (10.09.2004) US

(71) Applicant (for all designated States except US):  
**SHUR-LOK CORPORATION** [US/US]; 2541 White  
Road, Irvine, California 92614 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PATEL, Nilesh C.**  
[US/US]; 21 Iroquois Court, Irvine, California 92602  
(US).

(74) Agent: **PRICE, Joseph W.; SNELL & WILMER LLP**,  
600 Anton Boulevard, Suite 1400, Costa Mesa, California  
92626-7689 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,  
MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ,  
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,  
SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,  
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**


— as to applicant's entitlement to apply for and be granted a  
patent (Rule 4.17(ii))

**Published:**

— with international search report  
— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

[Continued on next page]

(54) Title: FLUID COUPLING ASSEMBLY WITH INTEGRAL RETENTION MECHANISM



(57) Abstract: The fluid coupling assembly for retaining a sealed joint includes the first member adapted to be connected to a first fluid conduit with a per sealing surface and a series of axially aligned serrations along with helical threads. A second member of a complementary configuration is adapted to be connected to a second fluid conduit with complementary threads and an axially extending cylindrical collar with spaced axial notches forming cantilevered beams. Each of the cantilevered beams can have teeth capable of engaging a series of serrations to provide an appropriate resistant force for both sealing engagement and disengagement. The teeth and serrations can remain in contact to provide a visual determination of a pretorqued force between the first member and the second member.

WO 2006/031386 A3



---

**(88) Date of publication of the international search report:**

13 July 2006

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*